



The firmware of A11-C has been upgraded to the New Firmware. It brings many new experiences, including the new stunning GUI, rock-solid stability, faster matching speed and better expandability.

A11-C

Users can easily manage data of A11-C via RS232/485, TCP/IP, and USB-host. Most importantly, all the functions can still operate in a networking state.

A11-C is compatibility with various types of USB flash disks, ADMS and former SDK. It also supports data backup and retrieve to avoid the risk of accidental deletion. It promotes the fingerprint time & attendance management to the next level. You can get the best of benefits from the A11-C.



SPECIFICATIONS

Fingerprint Capacity	3,000
Record Capacity	100,000
Card Capacity	10,000
Display	3-inch Screen
Communication	TCP/IP, RS232-485, USB-host
Standard Functions	Workcode, SMS, DST, Scheduled-bell, Self-Service Query, Automatic
	Status Switch ID/Mifare/HID, Webserver, External Printer, 9 digit user ID
Optional Functions	ADMS, USB-client
Power Supply	DC 5V 800mA
Verification Speed	≤1 Sec.
Operating Temp.	0 °C- 45 °C
Operating Humidity	20%-80%
Dimension	190 × 135.8 × 51.5mm (Length × Width × Thickness)
Net Weight	0.9 kg