

Proximity card based Wiegand reader (distance 10 cm) and optional Mifare card reader (distance 5cms) with external LED & Buzzer control.

Indoor / Outdoor Operation

Solid Epoxy Potted

Waterproof IP65

Reverse Polarity Protection

125 KHz Proximity/13.56MHz Mi-fare Card Reader

26/34bit Wiegand (Default)

External LED Control

External Buzzer Control

# TLRF6ER



## SPECIFICATION

Model	TLRF6ER	TLRF6MER
<b>Read Range</b>	Up to 10CM	Up to 5CM
<b>Reading Time (Card)</b>	≤300ms	
<b>Power / Current</b>	DC 6-14V / Max.70mA	
<b>Input Port</b>	2ea (External LED Control, External Buzzer Control)	
<b>Output Format</b>	26bit Wiegand (default)	34bit Wiega(default)
<b>LED Indicator</b>	2 Color LED Indicators(Red and Green)	
<b>Beeper</b>	Yes	
<b>Operating Temperature</b>	-20° to +65°C	
<b>Operating Humidity</b>	10% to 90% relative humidity non-condensing	
<b>Color</b>	Black	
<b>Material</b>	ABS+PC with texture	
<b>Dimension (W x H x T)mm</b>	75*116*16	
<b>Index of Protection</b>	<b>IP65</b>	